



Wi-Fi CERTIFIED™ Interoperability Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing.
Learn more: www.wi-fi.org/certification/programs



Certification ID: WFA50583

Page 1 of 2

| | |
|-----------------------------------|---|
| Date of Last Certification | February 12, 2014 |
| Company | D-Link Corporation |
| Product | Wireless AC1200 Dual Band Access Point |
| Model Number | DAP-1665 |
| Product Identifier(s) | |
| Category | Routers |
| Subcategory | Enterprise/Service Provider Access Point, Switch/Controller or Router |
| Hardware Version | Product: A1, Wi-Fi Component: A1 |
| Firmware Version | Product: 1.01, Wi-Fi Component: 1.01 |
| Operating System | Proprietary / Other: Embedded System |
| Frequency Band(s) | 2.4 GHz, 5 GHz - Concurrent |

Summary of Certifications

| CLASSIFICATION | PROGRAM |
|-----------------------|---------------------------------|
| Connectivity | Wi-Fi CERTIFIED™ a, b, g, n, ac |
| | WPA™ – Enterprise, Personal |
| | WPA2™ – Enterprise, Personal |
| Optimization | WMM® |
| | WMM®-Power Save |
| Access | Passpoint® |
| | Wi-Fi Protected Setup™ |



Security

WPA™ – Enterprise, Personal
WPA2™ – Enterprise, Personal
EAP Type(s)
EAP-TLS
EAP-TTLS/MSCHAPv2
PEAPv0/EAP-MSCHAPv2
PEAPv1/EAP-GTC
EAP-SIM
EAP-AKA
EAP-AKA Prime
EAP-FAST

Wi-Fi CERTIFIED™ a

Wi-Fi CERTIFIED™ b

Wi-Fi CERTIFIED™ g

Wi-Fi CERTIFIED™ n

2.4 GHz, 5 GHz - Concurrent
2 Spatial Streams 2.4 GHz
2 Spatial Streams 5 GHz
Short Guard Interval
TX A-MPDU
40 MHz operation in 2.4 GHz, with coexistence mechanisms
40 MHz operation in 5 GHz

Wi-Fi CERTIFIED™ ac

2 Spatial Streams 5 GHz
Rx MCS 8-9 (256-QAM)
Tx STBC 2x1
Rx A-MPDU of A-MSDU
Tx SU beamformer
Low Density Parity Check coding

WMM®

WMM®-Power Save

Passpoint®

Release 1

Wi-Fi Protected Setup™

2.4 GHz, 5 GHz - Concurrent
PIN
Push-Button (PBC)