



## Wi-Fi CERTIFIED™ Interoperability Certificate

This certificate lists the features that have successfully completed Wi-Fi Alliance interoperability testing.  
Learn more: [www.wi-fi.org/certification/programs](http://www.wi-fi.org/certification/programs)



**Certification ID: WFA66300**

**Page 1 of 2**

<b>Date of Last Certification</b>	July 14, 2020
<b>Company</b>	Cisco Systems
<b>Product</b>	Cisco 8510 WLAN Controller and Cisco AP3802 AP
<b>Model Number</b>	AIR-CT8510-K9 and AIR-AP3802
<b>Product Identifier(s)</b>	AIR-CT8510-K9 and AIR-AP3802 (SKU)
<b>Category</b>	Routers
<b>Subcategory</b>	Enterprise/Service Provider Access Point, Switch/Controller or Router
<b>Hardware Version</b>	Product: 1, Wi-Fi Component: 1
<b>Firmware Version</b>	Product: 8.10.128.64, Wi-Fi Component: 8.10.128.64
<b>Operating System</b>	Proprietary / Other: AireOS (controller) + Linux (...)
<b>Frequency Band(s)</b>	2.4 GHz, 5 GHz - Concurrent

### Summary of Certifications

<b>CLASSIFICATION</b>	<b>PROGRAM</b>
Connectivity	Wi-Fi CERTIFIED™ a, b, g, n, ac
	WPA2™ – Enterprise, Personal
	WPA3™ – Enterprise, Personal
	Wi-Fi Enhanced Open™
Optimization	Wi-Fi Vantage™
	WMM®
Access	Passpoint®



**Security**

WPA2™ – Enterprise, Personal  
WPA3™ – Enterprise, Personal (Aug 2019)  
EAP Type(s)  
Any EAP Type  
192-bit Security  
Protected Management Frames

**Wi-Fi CERTIFIED™ a**

**Wi-Fi CERTIFIED™ b**

**Wi-Fi CERTIFIED™ g**

**Wi-Fi CERTIFIED™ n**

2.4 GHz, 5 GHz - Concurrent  
3 Spatial Streams 2.4 GHz  
3 Spatial Streams 5 GHz  
Short Guard Interval  
TX A-MPDU  
40 MHz operation in 5 GHz  
HT Duplicate Mode (MCS 32)

**Wi-Fi CERTIFIED™ ac**

3 Spatial Streams 5 GHz  
Rx MCS 8-9 (256-QAM)  
Rx A-MPDU of A-MSDU  
Tx SU beamformer  
Low Density Parity Check coding  
Tx DL MU-MIMO  
Rx 160 MHz operations

**Wi-Fi Enhanced Open™**

**Wi-Fi Vantage™**

Release 1

**Wi-Fi Vantage™ (Release 1)**

**WMM®**

**Passpoint®**

Release 2

**Passpoint® (Release 2)**

Online Signup (OSU) and Policy Provisioning

**Spectrum and Regulatory Features**

802.11d